

Test Report

No. SDHG1305002119FT Date: May 20, 2013 Page 1 of 4

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description

: HINGE

Supplier Item No.

Manufacture

Supplier

Sample Receiving Date : May 15, 2013

Test Performing Date

: May 15, 2013 to May 20, 2013

Test Result Summary			
Test(s) Requested	Result(s)	Comments	
ISO 9227-2012	Grade 10	1	
For further details, please refer to the follo	wing page(s)		

Signed for and on behalf of SGS-CSTC Co., Ltd.

Jack Yao

Approved signatory

int is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ags.com/larms\_and\_conditions.electrons\_format decurrents\_eather\_to\_course its attention is grown to the Enranges of gradients and available in the Company and the Enranges of gradients and available in the Company and Enranges of gradients and pure district instructions. Flary The Company's cole responsibility is to be Client and this document does not attorned to the Company and the Enranges of gradients and the Enranges of gradients and the Enranges of Enranges of Client's Instructions. Flary The Company's cole responsibility is to be Client and this document does not attorned to a transaction of all their right, and obligations under the variancetion documents. This document cannot be reproducted except in this without prior written approval of the Company that alternative interpretation of the content of appearance of the document is unitarity and obligate may be proteosited to the full set except of the time of the content of

SDHG

# ("BildingEmpire InterniPet/le: Review Prat Versiches Lawn Text-Internitien (Imp.) 1 (86-757)22905888 | f (86-757)22905858 | 



Test Report

No. SDHG1305002119FT

Date: May 20, 2013

Page 2 of 4

## TESTS AND RESULTS

## Test Conducted:

ISO 9227-2012 Corrosion Tests in Artificial Atmospheres - Salt Spray Tests

## Scope:

This International Standard specifies the apparatus, the reagents and the procedure to be used in conducting the neutral salt spray (NSS), acetic acid salt spray (AASS) and copper accelerated acetic acid salt spray (CASS) tests for assessment of the corrosion resistance of metallic materials, with or without permanent or temporary corrosion protection.

It also describes the method employed to evaluate the corrosivity of the test cabinet environment,

It does not specify the dimensions of test specimens, the exposure period to be used for a particular product, or the interpretation of results. Such details are provided in the appropriate product specifications.

The salt spray tests are particularly useful for detecting discontinuities, such as pores and other defects in certain metallic, organic, anodic exide and conversion coatings.

The neutral salt spray test is the test method in which a 5 % sodium chloride solution in the pH range from 6,5 to 7,2 is atomized under a controlled environment. It particularly applies to:

- metals and their alloys.
- metallic coatings (anodic and cathodic),
- conversion coatings.
- anodic oxide coatings, and
- organic coatings on metallic materials.

The acetic acid salt spray test is the test method in which a 5 % sodium chloride solution with the addition of glacial acetic acid in the pH range from 3,1 to 3,3 is atomized under a controlled environment. It is especially useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic coatings on aluminum.

The copper accelerated acetic acid salt spray test is the test method in which a 5 % sodium chloride solution with the addition of copper chloride and glacial acetic acid in the pH range from 3,1 to 3,3 is atomized under a controlled environment. It is useful for testing decorative coatings of copper + nickel + chromium, or nickel + chromium. It has also been found suitable for testing anodic coatings on aluminum.

The salt spray methods are all suitable for checking that the comparative quality of a metallic material, with or without corrosion protection, is maintained. They are not intended to be used for comparative testing as a means of ranking different materials relative to each other with respect to corrosion resistance.

## General Test Condition:

The following test program was conducted in a laboratory environment maintained at 15 °C to 25 °C and 50%±5 RH. The sample was individually tested after conditioning in the test environment for at least 24 hours prior to conducting the test.

The complete detailed procedures may be found in the referenced specification and are only summarized herein. The results obtained for each of the applicable tests are presented in their respective section describing the procedures below.

This document is issued by the Company subject to its General Conditions of Service priviled overless, available on request or accessible at http://www.ags.com/error\_and\_conditions.

try: and, but electronic formal documents, subject to Terris and Conditions for Electronic Quarterests at away ags consistence endocument than Attention is drawn to the limitation of this documents and information continued the residence reflects the Company's Reflects and company and their regions under the archaestic formation from acceptance and the Company and their regions and ability and companies the regions and acting anomalises the archaestic formation from acceptance and the regions of the Company and the Company of the Company and the Company of the Company of the Company and the Company of the Company

SDHG

|子|「Resigiaryum hatemarketz | Parmeur Resignates | See | S