



‡Length of an elevator bolt is measured from the top of the head to the extreme end of the bolt.

ELEVATOR BOLTS											ANSI/ASME B18.5
Nominal Size	E		A			H		O		P	
	Body Diameter		Head Diameter			Head Height		Square Width		Square Depth	
	Max.	Min.	Max. Edge Sharp	Min. Edge Sharp	Min. Edge Flat	Max.	Min.	Max.	Min.	Max.	Min.
1/4	0.260	0.237	1.008	0.969	0.938	0.098	0.078	0.280	0.245	0.219	0.188
5/16	0.324	0.298	1.227	1.188	1.157	0.114	0.094	0.342	0.307	0.250	0.219
3/8	0.388	0.360	1.352	1.312	1.272	0.145	0.125	0.405	0.368	0.250	0.219

  

Tolerance on Length	Nominal Bolt Size	Nominal Bolt Length		
		Up to 1 in., incl.	Over 1 in. to 2-1/2 in., incl.	Over 2-1/2 in. to 4 in., incl.
		1/4 thru 3/8	+0.02, -0.03	+0.02, -0.04

<b>Description</b>	Bolt with a wide, countersunk flat head, a shallow conical bearing surface, an integrally-formed square neck under the head, and a unified thread pitch.
<b>Applications/ Advantages</b>	Popular use is in conveyor systems.
<b>Material</b>	AISI 1006 - 1050 or equivalent steel.
<b>Core Hardness</b>	1/4 through 3/8 in. diameter, all lengths: Rockwell B70 - B100
<b>Proof Load</b>	1/4 through 3/8 in. diameter, all lengths: 33,000 psi.
<b>Yield Strength</b>	1/4 through 3/8 in. diameter, all lengths: 36,000 psi. minimum
<b>Tensile Strength</b>	1/4 through 3/8 in. diameter, all lengths: 54,000 psi. minimum
<b>Elongation</b>	18% minimum (all sizes)
<b>Reduction of Area</b>	35% minimum (all sizes)
<b>Minimum Thread Length</b>	The minimum length of thread shall be equal to twice the basic bolt diameter plus 0.25 in..
<b>Plating</b>	See Appendix-A for plating information.