

METRIC





est. / 1946







METRIC - JIS-B1111 SMALL PAN HEAD PHILLIPS MACHINE SCREW JIS-B1111										
	Thread 19 Pitch	А		H1		М	G			
Nominal Size est.		Head Diameter		Height of Head		Recess Diameter	Recess Gauge Penetration		Phillips Driver Size	
		Max	Min	Max	Min	Ref	Max	Min		
МЗ	0.5	5.5	5.0	2.15	1.85	3.6	1.43	0.86	2	
M4	0.7	7.0	6.5	2.75	2.45	4.2	2.03	1.45	2	
M5	0.8	9.0	8.4	3.45	3.15	4.9	2.73	2.14	2	
M6	1	10.5	9.8	4.1	3.7	6.3	2.86	2.26	3	
EITTII								NG		
Tolerance on Length			Nominal Diameter		Nominal Screw Length					
					4mm or under	Over 4mm to 10mm	Over 10mm to 20mm	Over 20mm to 40mm	Over 40mm	
			M3 and M4		-	-0.6	-0.6	-0.8	-1	
			M5 and M6		-	-0.8	-1	-1/	-1	

Description	A pan head, straight shank fastener with a metric thread pitch designed to go through a hole or nut that is pre-tapped to form a mating thread for the screw. The height and diameter of the pan head are between 5 and 20% smaller than a standard pan head.					
Applications/ Advantages	The "Small Pan" head machine screw per JIS-B1111 is a preferred design for use in small electronic components where there is limited clearance area. The M3 and M4 diameters also meet the requirements of SN 213307 Cheese head screws.					
Material	Class 4.8 machine screws shall be made from a carbon steel, partially or fully annealed as required, which conforms to the following chemical composition <i>Carbon</i> : 0.55% maximum; <i>Phosphorus</i> : 0.05% maximum; <i>Sulfur</i> : 0.06% maximum.					
Hardness	Rockwell B 71 - 99.5 (Vickers HV 130 - 250)					
Tensile Strength	420 N/mm² minimum					
Plating	Parts are typically provided with a clear zinc finish.					