



Pan; Six-Lobe & Combo

HEAD DIMENSIONS





SUPPLY CORP.

est. / 1946

SIX-LOBE PAN HEADS

ASME B18.6.3-2013

Screw Size	D		H		R	G		(Fallaway) Max Penetration	Driver Size	
	Head Dimensions					Recess Dimensions				
	Head Diameter		Head Height		Diameter	Gauge Penetration				
	Max	Min	Max	Min	Ref	Max	Min			
0	.116	.104	.044	.036	.058	.020	.015	.009	T5	
2	.167	.155	.062	.053	.094	.035	.030	.019	T8	
3	.193	.180	.071	.062	.094	.038	.033	.019	T8	
4	.219	.205	.080	.070	.111	.045	.035	.022	T10	
5	.245	.231	.089	.079	.111	.055	.045	.022	T10	
6	.270	.256	.097	.087	.132	.055	.045	.026	T15	
8	.322	.306	.115	.105	.155	.070	.055	.031	T20	
10	.373	.357	.133	.122	.178	.085	.070	.036	T25	
12	.425	.407	.151	.139	.200	.085	.070	.040	T27	
14	.476	.457	.169	.156	.221	.075	.060	.044	T30	
1/4	.492	.473	.175	.162	.221	.100	.085	.044	T30	
5/16	.615	.594	.218	.203	.266	.120	.105	.047	T40	
3/8	.740	.716	.261	.244	.312	.145	.130	.055	T45	



SUPPLY CORP.

est. / 1946

PHILLIPS AND SLOTTED COMBINATION DRIVE PAN HEADS

ASME B18.6.3-2013

Nominal Screw Size	G		H		J		A		M	Recess Penetration Gaging Depth		Phillips Driver Size
	Head Dimensions					Slot Dimensions				Recess Dimensions		
	Head Diameter		Head Height		Width		Depth		Diameter	Max	Min	
	Max	Min	Max	Min	Max	Min	Max	Min	Ref	Max	Min	
4	.219	.205	.080	.070	.039	.031	.040	.027	.115	.071	.053	1
6	.270	.256	.097	.087	.048	.039	.050	.033	.159	.080	.055	2
7	.296	.281	.106	.096	.048	.039	.054	.036	.170	.089	.064	2
8	.322	.306	.115	.105	.054	.045	.058	.041	.175	.097	.071	2
10	.373	.357	.133	.122	.060	.050	.068	.048	.192	.113	.089	2
12	.425	.407	.151	.139	.067	.056	.077	.055	.252	.124	.098	3
14	.476	.457	.169	.156	.075	.064	.085	.060	.274	.144	.118	3
1/4	.492	.473	.175	.162	.075	.064	.087	.063	.274	.144	.118	3
5/16	.615	.594	.218	.203	.084	.072	.106	.076	.343	.173	.149	4