



GE
Lighting

93404 - GE Ecolux® Blax® T4 - Facilities; Retail Display; Hospitality;
Office; Restaurant; Warehouse

F57QBX850A4P/EOL

☞ Super long life

Product Photo



GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	-20 °C
Mercury-Picogram per mean lm hr	47.7
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	GX24q-5
Bulb Shape	PAR38

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	3700 lm
Nominal Initial Lumen per Watt	75
Initial Lumens-nominal	4300 lm
Color Rendering Index-CRI	82
Color Temperature	5000 K

PRODUCT INFORMATION

Product Code	93404
Description	F57QBX850A4P/EOL
Alternative Unit Of Measure	CASE

DIMENSIONS

Nominal Length	5.2 in
Bulb Max Overall Length-MOL	5.2 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	200 W
Supply Current Freq nominal Hz	20 Hz
Rated power (Watts)	57 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).