

97580 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse F18DBX/841/ECO

Product Photo



GENERAL CHARACTERISTICS

Base Type Mercury Content Rated Life Hours-nominal Starting Temp (MIN) C-degrees Mercury-Picogrm per mean Im hr Primary Application Pin/Plug-In

3 mg

10000 h

-15 °C

306.1

Facilities

Retail Display

Hospitality Office

Restaurant Warehouse

G24d-2

980 lm

67 1200 lm

82

4100 K

97580

EACH

F18DBX/841/ECO

A19

Compact Fluorescent

Product Technology Base Bulb Shape

PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal Nominal Initial Lumen per Watt Initial Lumens-nominal Color Rendering Index-CRI Color Temperature

PRODUCT INFORMATION

Product Code Description Alternative Unit Of Measure

DIMENSIONS

Base Face to Top of Lamp	5.16 in
Nominal Length	6.1 in
Bulb Max Overall Length-MOL	6.06 in

ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	65 W
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	18 W

CAUTIONS & WARNINGS

Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

NOTES

Based on 60Hz reference circuit.

Aug 17, 2016 5:45:34 PM For additional information, visit www.gelighting.com