

Constant-temperature Incubator

◎ High precision experimental bacterial incubator.

Characteristics:

- Unique vertical double duct supply horizontal air circularly.
- 4 grades 3 speed adjustable speed fan, LED running indicator light.
- Over-temperature protection system: LED red light on meanwhile cut off heating circuit to improve product safety when workroom temperature exceed the alarm value.
- High precision digital independent temperature limiter.



Patent No. : ZL 2018 3 0095051.6

Main Technical Parameters:

Model	WPL-30BE	WPL-45BE	WPL-65BE	WPL-85BE	WPL-125BE	WPL-230BE					
Cycle Mode	Forced convection										
Function	Temp. range	RT+5~120°C									
	Temp. Resolution Ratio	0.1°C									
	Temp. Motion	± 1°C									
	Temp. Uniformity	± 1.0°C									
Structure	Inner Chamber	Mirror Stainless Steel									
	Outer Shell	Cold rolling steel electrostatic spraying exterior									
	Insulation layer	High quality foam board									
	Heater	Stainless steel heater									
	Power rating	0.4kW	0.5kW	0.7kW	0.9kW	1.1kW	1.5kW				
	Exhaust hole	φ 28mm top(with function of test hole)									
Controller	Temp control mode	Two temperature section intelligent PID									
	Temp. setting mode	Touch button setting									
	Temp. display mode	Measuring temperature: LCD upper screen; setting temperature: the lower row									
	Timer	0~9999min(with timing wait function)									
	Operation function	Fixed temperature operation, timing function, auto stop.									
	Additional function	Sensor deviation correction, temperature overshoot self-tuning, internal parameter locking, power-off parameter memory									
	Sensor	pt100									
Specification	Inner Chamber size(W*L*H)(mm)	310*310*310	350*350*350	400*360*450	450*420*450	500*450*550	600*500*750				
	Exterior size (W*L*H)(mm)	460*510*695	500*550*735	550*550*840	590*610*830	636*680*915	730*680*1250				
	Packing size (W*L*H)(mm)	550*585*845	590*625*885	640*635*985	690*695*985	740*725*1085	860*790*1400				
	Volume	30L	45L	65L	85L	125L	230L				
	Shelf number	6	7	9	9	13	17				
	Load per rack	15kg									
	Shelf space	35mm									
	Current rating	220V/3.6A	220V/5.5A	220V/7.2A	220V/9.0A	220V/10.5A	220V/13.6A				
	NW/GW (kg)	33/37	37/43	44/49	50/56	60/66	94/120				
Accessory	Shelf	2									
Optional accessories		Refer to Page 42									