Giada DN72

Cost-Effective ARM CPU Media Player for Digital Signage

Features

◆ Support RK3288 Quad Core A17 CPU
◆ Onboard DDR3L, Up to 2GB
◆ 1 x HDMI Display Port with 4K Resolution
◆ Onboard 16GB EMMC + 1 x TF Card Reader
◆ 4 x USB2.0, 1 x RJ45, 1 x RS232, 1 x SIM Slot for 3G/4G
◆ 1 x Mini-PCIe for WiFi/BT/3G/4G

Specifications

RoHS C€ FC ⟨CC⟩

		Giada DN72
Processor	CPU	RK3288 Quad Core A17 CPU
	Frequency	Up to 1.8GHz
	Chipset	SOC
Memory	Type	DDR3L-1333MHz
	Socket	Onboard
	Size	2GB
Graphics	GPU	ARM Mali-T764
	Graphic Engine	4K H.264/H.265 video decoder, 1080P video encoder/1080P 60fps video decoders
	HDMI	1 x HDMI (Max. 3840 x 2160 @60 Hz)
Network	Controller	Realtek RTL8211E Gigabit Ethernet
	Interface	1 x RJ45
I/O	USB	3 x USB 2.0, 1 x USB2.0 OTG
	Display Interface	1 x HDMI
	LAN	1 x RJ45
	Serial Port	1 x RS232
	Audio	1 x MIC-IN, 1 x AUDIO-OUT
	Mini-PCIe1#	1 x Full-size Mini-PCIe for WiFi/BT/3G/4G（Only USB）
	SIM	1 x SIM Slot for 3G/4G
	JAHC Switch	1
	LED Indicators	1 x HDD LED, 1 x Power LED
	WiFi+BT on Board	1 x WiFi + BT Module Onboard (Optional)
Storage	EMMC	Onboard, 16GB
	Card Reader	1 x TF Card Reader
JAHC Tech	WatchDog Timer	0~255 Second Time Out Support
	Auto Power On	Power Activated Automatically Start
	RTC	Set Up Independently Every day, A Week as a Cycle
	Remote Control	By IR Controller for Power On
	Wake On Lan	Yes
Operation System	Android	Android 5.1

		Giada DN72
Power	Power Type	DC-IN
	Power Adapter	12V/2A
Mechanical	Dimensions (W x D x H)	116.6mm x 107.2mm x 30mm
	Fanless	Yes
	Construction	Metal
	Mounting	Desk/Wall Mounting and VESA Mounting Kit (Optional)
	Color	Black
Environment	Operating Temperature	0℃ ~ 40℃ (32 ℉ ~ 104 ℉) at 0.7m/s Air Flow
	Relative Humidity	95% @ 40℃ (non-condensing)
Certification	Certification	CE, FCC Class B, CCC