

Skydro ceiling 2-wire dimming

SPECIFICATIONS

1245118A



Design By

Ross Lovegrove

Collection

Design



Specifications

Delivered lumens	1300lm
Light output ratio	45lm/W
Power consumption	29W
Led type	27W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>93
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 1 x XTC32-0700P-UNV-I

**Reverse or forward phase (120v only)

Colors & Finishes

Polished Aluminum


Materials

- Reflective unit in ABS injection-molded mirror treated
- Lighting unit in die-cast aluminum mirror treated
- Bearing structure in painted steel

Features & Accessories

- Without integrated lighting unit (non-electrified)
- Optional template available to help assemble multiple units
- Possible to obtain a numerous range of configurations simply by adding extra units

Dimensions




Packaging

1 Box

1 x 34-3/4" x 30" x 26-7/8" / 52.03 lbs - 88 cm x 76 cm x 68 cm / 23.6 kg

Light distribution

Indirect



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

29.67 lbs / 13.46 kg

Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.