

Altrove 600 suspension direct/indirect

SPECIFICATIONS

1540118A



Design By

Carlotta de Bevilacqua

Collection

Design



Specifications

Delivered lumens	N/A
Light output ratio	N/A
Power consumption	80W
Led type	36.1W Array* + 34.9W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire (Tu-wire)
Input Voltage	120V
Driver	ADVANCE - 2 x XR054C150V054RNT1

Colors & Finishes

- Aluminum (Structure)
- Transparent (Diffuser)


Materials

- Perimeter structure in mirror stainless steel
- Lateral diffusers in matte finish prismoptic
- Reflector in mirror polished aluminum
- Bottom diffuser in engraved transparent methacrylate

Features & Accessories

- Dimmer White Tu-Wire (W001-00352)

Dimensions



Packaging

1 Box

1 x 30" x 30" x 10-3/4" / 26.46 lbs - 76 cm x 76 cm x 27 cm / 12 kg

Light distribution

Direct/Indirect

Luminaire weight

19.4 lbs / 8.8 kg

Warranty

5 year Limited warranty,
Upon registration. Click here
to register your purchase.