Ameluna suspension

SPECIFICATIONS



Design By 🗕

Artemide Mercedes-Benz Style

Collection

Design



Colors & Finishes

Transparent (Body)

Materials =

- Body in high transparency injection-molded PMMA
- Lower ring of body in PMMA with opaline finish

Features & Accessories

Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

CRI (Color Rendering Index)

• Ameluna discloses an innovative optoelectronic system integrated in the transparent frame

2994.91lm

65.1lm/W

39.1W Array*

46W

3000K

50000Hrs

Dimmable 2-Wire


HATCH - 1 x LC40-2100P-120-G

>90

120V

- Heatsink is an extrusion that runs all around the body and hosts the LED strips
- Light reflected by thin PMMA element and then diffused by ring of opaline PMMA

Dimensions =



Light distribution =

Direct

Luminaire weight —

16.53 lbs / 7.5 kg

Warranty

5 year limited warranty, Upon registration. Click here to register your purchase.

Packaging •

1 Box

1 x 35-1/2" x 35-1/2" x 13-7/8" / 31.97 lbs - 90 cm x 90 cm x 35 cm / 14.5 kg

