

Calumet 8 double wall 2x8.5° 3000K white

SPECIFICATIONS

T41922NW08



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

Delivered lumens	369lm
Light output ratio	46.13lm/W
Power consumption	8W
Led type	7.5W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	TCl - 1 x DCC-15W-350MA/US
BUG Rating	B1-U3-G0

Colors & Finishes

White RAL9002


Materials

- Diffuser in reinforced glass
- Body in aluminum

Features & Accessories

- Direction of light beam can be adjusted to obtain desired lighting effect on wall
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions



Packaging

1 Box


1 x 13-7/8" x 8-9/16" x 10-5/16" / 5.22 lbs - 35 cm x 21.5 cm x 26 cm / 2.37 kg

Light distribution

Direct/Indirect

Luminaire weight

3.73 lbs / 1.69 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.