

Calumet 13 double wall 2x9° 4000K white

SPECIFICATIONS

T41952NN08



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

Delivered lumens	744lm
Light output ratio	46.5lm/W
Power consumption	16W
Led type	15W Array*
CCT (Correlated Color Temperature)	4000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120-277V
Driver	MAGTECH - 1 x LP1020-36-C0500
BUG Rating	B1-U3-G0

Colors & Finishes

White RAL9002


Materials

- Diffuser in reinforced glass
- Body in aluminum

Features & Accessories

- Direction of light beam can be adjusted to obtain desired lighting effect on wall
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions



Packaging

1 Box


1 x 20" x 13-3/8" x 14-3/8" / 12.35 lbs - 50.7 cm x 33.7 cm x 36.3 cm / 5.6 kg

Light distribution

Direct/Indirect

Luminaire weight

8.38 lbs / 3.8 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Warranty

5 year limited warranty, Upon registration. Click here to register your purchase.