

Ciclope 50 bilateral floor white

SPECIFICATIONS

T081308



Design By

Alessandro Pedretti

Collection

Outdoor



Specifications

Delivered lumens	568lm
Light output ratio	43.69lm/W
Power consumption	13W
Led type	2X6W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	TCI - 2 x DCC-15W-350MA/US
BUG Rating	B0-U3-G1

Colors & Finishes

White RAL9002


Materials

- Body in aluminum
- Diffuser in light-diffusing polycarbonate
- Ground mounting plate in steel

Features & Accessories

- Electronic driver included
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions



Packaging

1 Box


1 x 9-9/16" x 9-9/16" x 24-11/16" / 11.9 lbs - 24 cm x 24 cm x 62.5 cm / 5.4 kg

Light distribution

Diffused

Luminaire weight

9.92 lbs / 4.5 kg



Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane