

Demetra micro wall

1748028A

SPECIFICATIONS



Design By

Naoto Fukasawa

Collection

Design



Specifications

Delivered lumens	257lm
Light output ratio	36.7lm/W
Power consumption	7W
Led type	6W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Colors & Finishes

☐ White


Materials

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Wall support in painted aluminum

Features & Accessories

- Fully adjustable arms and head
- Tilttable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions




Packaging

1 Box

1 x 19-9/16" x 8-9/16" x 5-3/16" / 2.07 lbs - 49.5 cm x 21.5 cm x 13 cm / .94 kg

Light distribution

Direct



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

1.21 lbs / .55 kg

Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.