DEM1025



Design By =

Naoto Fukasawa

Collection =

Design







Colors & Finishes =



Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- Table clamp made in die-cast aluminum with matching painted finish


Specifications =

Delivered lumens	392lm
Light output ratio	43.56lm/W
Power consumption	9W
Led type	8.5W Array*
CCT (Correlated Color Temperature)	2700K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Features & Accessories =


- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions =



Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 5-3/16" x 4-13/16" x 3-5/8" / .44 lbs - 13 cm x 12 cm x 9 cm / .2 kg

Luminaire weight 1.54 lbs / .7 kg

5 cm

table thickness min. 1/4" - max. 2 ^{1/16}" min. 0.7 cm - max. 5.2 cm clamp length min. 3 ^{11/16}" - max. 5 ^{7/16}"

2 ^{3/8}" min. 9.4 cm - max. 13.9 cm

Warranty =

5 year limited warranty, Upon registration. Click here to register your purchase.

