DEM1042



Design By =

Naoto Fukasawa

Collection =

Design







Colors & Finishes =

	1
	White

Specifications —

Delivered lumens	392lm
Light output ratio	43.56lm/W
Power consumption	9W
Led type	8.5W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal tension springs and external tension control cables in aluminum
- In-set pivot made in die-cast aluminum with matching painted finish

Features & Accessories

- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions =



46.5 cm

1" ## 2.5 cm min. 3/8" - max. 2 ^{1/4}" min. 0.37 cm - max. 5.7 cm | 15.5 cm | 2 1 13/16" | 7 cm required hole: Ø 3/4" - Ø1.9 cm | 1 3/16" | 7 cm


Luminaire weight

1.54 lbs / .7 kg

Warranty
5 year limited warranty,
Upon registration. Click here
to register your purchase.

Light distribution

Direct



Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

Packaging =

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 5-3/16" x 5-3/16" x 3-5/8" / .44 lbs - 13 cm x 13 cm x 9 cm / .2 kg

