Demetra table with inset pivot

DEM1058

DIMMABLE (On Head) / No Motion Sensor



• Head and arms in painted aluminum

• Lower head diffuser in thermoplastic

• Wall support in painted aluminum

• Internal tension springs and external tension control cables in aluminum

Design By Maoto Fukasawa

Collection

Design





Colors & Finishes =

Matte Black

Materials =

Features & Accessories =

Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

CRI (Color Rendering Index)

· Fully adjustable arms and head

• Tiltable and rotatable diffuser

• Interchangeable plug options accommodate most electrical outlets for global versatility

392lm

9W 8.5W Array*

2700K

>90


50000Hrs

120-240V

Plug-In

43.56lm/W


Dimensions =



22 ^{7/6}" 57 cm <u>24 ^{1/2}"</u> 62 cm

Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging

2 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 5-3/16" x 5-3/16" x 3-5/8" / .44 lbs - 13 cm x 13 cm x 9 cm / .2 kg

Luminaire weight

Warranty •

1.54 lbs / .7 kg

min. 3/8" - max. 2 ^{1/4}" min. 0.37 cm - max. 5.7 cm required hole: ø 3/4" - ø1.9 cm

> 5 year limited warranty, Upon registration. Click here to register your purchase.

ø 1″ ø 2.5 cm

1 9/16"

. 4 cm

9/16" 1.5 cm 2 ^{13/16}" 7 cm

last updated: 2019-03-28

We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

