

Ego 55 downlight square 16°x34° 3000K

SPECIFICATIONS

T4060ELPTW08



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

Delivered lumens	71lm
Light output ratio	47.33lm/W
Power consumption	1.5W
Led type	1.3W ARRAY
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	24VDC
Driver	Remote power supply (sold separately)
BUG Rating	B0-U0-G0

Colors & Finishes

Stainless Steel


Materials

- Body in aluminum
- Frame in stainless steel
- Black silkscreened tempered glass
- Swing arms to fasten to ceiling in steel

Features & Accessories

- Fastened to ceiling by swing arms
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative
- 24V DC supply required (remote driver sold separately)
- Transformer 40W 24Vdc (TE00-00037)
- Transformer 40W 24Vdc (TE00-00037)

Dimensions



Packaging

1 Box


1 x 7-15/16" x 7-15/16" x 6-13/16" / 1.19 lbs - 20 cm x 20 cm x 17 cm / .54 kg

Light distribution

Direct

Luminaire weight

.62 lbs / .28 kg



Warranty

5 year limited warranty, Upon registration. Click here to register your purchase.

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane