## T4082SPN08



# Design By —

Ernesto Gismondi

## Collection —

Outdoor





## Colors & Finishes =



# Materials =

- Body in aluminum
- Frame in stainless steel
- Black silkscreened tempered glass
- Swing arms to fasten to ceiling in steel

### Specifications ———

| Delivered lumens                   | 201lm                                 |
|------------------------------------|---------------------------------------|
| Light output ratio                 | 57.43lm/W                             |
| Power consumption                  | 3.5W                                  |
| Led type                           | 3W ARRAY                              |
| CCT (Correlated Color Temperature) | 4000K                                 |
| CRI (Color Rendering Index)        | >80                                   |
| Life expectancy                    | 50000Hrs                              |
| Control type                       | On/Off                                |
| Input Voltage                      | 24VDC                                 |
| Driver                             | Remote power supply (sold separately) |
| BUG Rating                         | B0-U0-G0                              |

#### Features & Accessories =

- Fastened to ceiling by swing arms
- Adjustable range: tilt +/-8°
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative
- 24V DC supply required (remote driver sold separately)
- Transformer 40W 24Vdc (TE00-00037)
- Transformer 40W 24Vdc (TE00-00037)

### Dimensions ==


# Packaging =

Boxes



# Light distribution -

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

# Luminaire weight -

N/A

## Warranty =

5 year limited warranty, Upon registration. Click here to register your purchase.

