T4082SPW08



Design By —

Ernesto Gismondi

Collection —

Outdoor







Colors & Finishes =



Materials =

- Body in aluminum
- Frame in stainless steel
- Black silkscreened tempered glass
- Swing arms to fasten to ceiling in steel

Specifications ———

Delivered lumens	201lm
Light output ratio	57.43lm/W
Power consumption	3.5W
Led type	3W ARRAY
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	24VDC
Driver	Remote power supply (sold separately)
BUG Rating	B0-U0-G0

Features & Accessories =

- Fastened to ceiling by swing arms
- Adjustable range: tilt +/-8°
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative
- 24V DC supply required (remote driver sold separately)
- Transformer 40W 24Vdc (TE00-00037)
- Transformer 40W 24Vdc (TE00-00037)

Dimensions ==


Packaging =

Boxes



Light distribution -

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight

N/A

Warranty =

5 year limited warranty, Upon registration. Click here to register your purchase.

