

Lineacurve 36 mono wall/ceiling 2-wire dimming

SPECIFICATIONS

RDLC3D93506W



Design By

NA Design

Collection

Design



Specifications

| | |
|------------------------------------|-------------------------------|
| Delivered lumens | 1280lm |
| Light output ratio | 43.5lm/W |
| Power consumption | 29.4W |
| Led type | 25W Array* |
| CCT (Correlated Color Temperature) | 3500K |
| CRI (Color Rendering Index) | >90 |
| Life expectancy | 50000Hrs |
| Control type | Dimmable 2-Wire** |
| Input Voltage | 120-277V |
| Driver | HATCH - 1 x XTC34-1050P-UNV-I |

**Reverse or forward phase (120v only)

Colors & Finishes

White


Materials

- Body in extruded aluminum
- End caps in aluminum

Features & Accessories

- Extrusion covers junction box dimension

Dimensions



Packaging

1 Box

1 x 40-5/16" x 8-1/16" x 5-1/16" / 10.43 lbs - 102.24 cm x 20.32 cm x 12.7 cm / 4.73 kg

Light distribution

Direct

Luminaire weight

8.62 lbs / 3.91 kg

Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.