

# Lineacurve 36 dual wall/ceiling 2-wire dimming

## SPECIFICATIONS

RDLC3B93506AN



### Design By

NA Design

### Collection

Design



### Specifications

Delivered lumens	2560lm
Light output ratio	44lm/W
Power consumption	58.8W
Led type	2X25W Array*
CCT (Correlated Color Temperature)	3500K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 2 x XTC34-1050P-UNV-I

\*\*Reverse or forward phase (120v only)

### Colors & Finishes

■ Anthracite grey


### Materials

- Body in extruded aluminum
- End caps in aluminum

### Features & Accessories

- Extrusion covers junction box dimension

### Dimensions




### Packaging

1 Box

1 x 40-5/16" x 8-1/16" x 5-1/16" / 10.43 lbs - 102.24 cm x 20.32 cm x 12.7 cm / 4.73 kg

### Light distribution

Direct/Indirect



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

### Luminaire weight

8.62 lbs / 3.91 kg

### Warranty

5 year limited warranty, Upon registration. Click here to register your purchase.