

Lunex 15 wall/ceiling LED 13W 2-wire dimming

SPECIFICATIONS

RD502410



Design By

Peclar Nalbandian & Guy Burr

Collection

Design



Specifications

| | |
|------------------------------------|-------------------------------|
| Delivered lumens | 500lm |
| Light output ratio | 38.46lm/W |
| Power consumption | 13W |
| Led type | 12W Array* |
| CCT (Correlated Color Temperature) | 3000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | Dimmable 2-Wire** |
| Input Voltage | 120-277V |
| Driver | HATCH - 1 x XTC32-0700P-UNV-I |

Colors & Finishes

Opal white

Materials


- Diffuser in opaline handblown glass.
- Mounting plate in powder coated steel with steel fasteners.

**Reverse or forward phase (120v only)

Features & Accessories

- Mounting to standard junction boxes centered on luminaire

Dimensions



Packaging


2 Boxes

Light distribution

Diffused

Luminaire weight

.02 lbs / .01 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Warranty

5 year limited warranty,
Upon registration. Click here
to register your purchase.