Mercury mini LED suspension 2-wire dimming 1477118A

SPECIFICATIONS

1346lm

46lm/W

29W 24W C.O.B.*

3000K

50000Hrs

120-277V

Dimmable 2-Wire**

HATCH - 1 x XTC32-0700P-UNV-I

>93



Design By = Ross Lovegrove

Collection = Design



Colors & Finishes

Polished Aluminum (Pebbles)

Stainless Steel (Reflector)

Materials =

- Lighting unit in die-cast aluminum
- Reflective units made of injection-molded thermoplastic material with metallic finish

Standard length

Min. 3715/16" - Max. 10215/16" Min. 96.4 cm - Max. 261.4 cm Extended length

Min. 37^{15/16}" - Max. 215³⁴" Min. 96.4 cm - Max. 548 cm

• Reflector in stainless steel

Dimensions =

1 33/4 35 cm

22^{3/8}" 56.9 cm

1 Box

Packaging =

Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

**Reverse or forward phase (120v only)

Features & Accessories

• Custom applications available


CRI (Color Rendering Index)

1 x 31-9/16" x 31-9/16" x 9-15/16" / 31.42 lbs - 80 cm x 80 cm x 25 cm / 14.25 kg

Light distribution =

Indirect

ø 27^{9/16}″ ø 70 cm



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane Luminaire weight

23.7 lbs / 10.75 kg

Warranty =

5 year limited warranty, Upon registration. Click here to register your purchase.

