

# Obice wall 34°

T430534W28

## SPECIFICATIONS



### Design By

Alessandro Pedretti

### Collection

Outdoor



### Specifications

Delivered lumens	605lm
Light output ratio	60.5lm/W
Power consumption	10W
Led type	8W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x LPC-20-700
BUG Rating	B1-U0-G0

### Colors & Finishes

White


### Materials

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

### Features & Accessories

- Tilting angle +35°/-125°
- Rotation on horizontal axis 359°
- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

### Dimensions



### Packaging

1 Box


1 x 12-11/16" x 12-11/16" x 8-9/16" / 5.25 lbs - 32 cm x 32 cm x 21.5 cm / 2.38 kg

### Light distribution

Direct

### Luminaire weight

3.86 lbs / 1.75 kg



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

### Warranty

5 year limited warranty, Upon registration. Click [here](#) to register your purchase.