

Obice mini wall 34°

T430434W18

SPECIFICATIONS



Design By

Alessandro Pedretti

Collection

Outdoor



Specifications

Delivered lumens	460lm
Light output ratio	65.71lm/W
Power consumption	7W
Led type	7W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	24VDC
Driver	Remote power supply (sold separately)
BUG Rating	B1-U0-G0

Colors & Finishes

Black


Materials

- Body in injection molded aluminum
- Terminal base and adjustable joint in injection molded aluminum
- Diffuser in 1/64" (4mm)-thick tempered glass with black opal serigraphy

Features & Accessories

- Tilting angle +35°/-125°
- Rotation on horizontal axis 359°
- Wiring to be carried out by means of a plug located in the terminal base
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative
- ()
- Transformer 24vDC 60W 120v (TE01-11575)

Dimensions




Packaging

1 Box

1 x 12-11/16" x 12-11/16" x 8-9/16" / 4.33 lbs - 32 cm x 32 cm x 21.5 cm / 1.965 kg

Light distribution

Direct



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

2.79 lbs / 1.27 kg

Warranty

5 year limited warranty, Upon registration. Click here to register your purchase.